

Glass Fiber Packing with Graphite Impregnation

Code: KXTP802



Description

The packing square braided from E-glass impregnated with graphite. Good frictional factor.

KXT-P802S -- Glass Fiber Packing with Graphite Impregnation reinforced with SS Wire



Item no.: KXTP802

Glass Fiber Packing with Graphite Impregnation
Item no.: KXTP802

- * Low maintenance, easy to control
- * Excellent capabilities of high strength and high temperature resistance
- * Economical packing

Typical Application

- * Universal packing, especially suitable for a wide range of applications for large rotary pumps in the medium pressure range
- * Suited for chemical neutral and resistant to water, steam, hot air, oils, etc.

Technical Data

Material		E-glass fiber
Temperature Range		-100 up to +600 oC atmosphere.
Process	Rotating	20 bar
	Reciprocating	40 bar
	Static	80 bar
Shaft Speed		20 m/s in rotary
PH		5~9
Density		0.75~1.25 g/cm3

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,

Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com